

TOLUENE Pure. C6H5.CH3 210 Kg

Part No. RXSOL-19-1449-210 — Generated 29 Sep 2026

1. Product and Company Identification

Product Name : RXSOL-19-1449-210
Product Type : TOLUENE Pure. C6H5.CH3 210 Ltr
Chemical Family : Aromatic Hydrocarbon
Product Description : Clear Colourless

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA
Stock Point ::: Kandla, Mumbai, Kolkata, Chennai, Visakhapatnam, Fujairah

Phone : +91 22 27815541 / 42
Fax : +91 22 2781 1318 :::AOH :0091 9821214367
Email : mail@rxmarine.com

2. Composition / informationon ingredients

Name	CAS#	% by Weight
Toluene	F, Xn, R11, R20	99.89

3. Hazards Identification

Health Hazards	Harmful by Inhalation
Physical / Chemical And Fire Exploslon	From Flamable Mixtures.

4. First Aid Measures

Inhalation, Skin Contact, Eye Contact, Ingestion.

5. Fire-fighting Measures

Procedure	Use Water Spray To Cool Fire Exposed, Surfaces, Protect Personal, and Shut Of "Fuel" to Fire.Allow Fire To Burn Under Controlled Conditions, Extinguish With Alcohol Type Foam or Dry Chemical. Cover Liquid Spill With Foam.
-----------	---

6. Accidental Release Measures

- Eliminate Ignition Sources. Prevent Liquid Enters Sewers, Water Sources, Low Area.
- Spill With Sand Earth . Dilute Contalend Spill With Water. Dispose Recover Material Conforms To local Regulation.
- Keep Public Away.

7. Handling and Storage

Storage / Transport Temperture :
Amblent

Loading / Unloading Trempreture: Amblent

Loading / Unloading Viscosity: 0.64

Storage / Transport Pressure: Atmospheric

Electrostatics Accumulation Hazards:
Yes

Shipping Containers: Rall Wagons, Tanks Trucks, Tankers, Burges, Drums.

Materials Suitable : Carbon Steel,
Stainless Still, Polyesters, Teflon.

Materials Unsuitable: Natural Rubber, Butyl Rubber, EPDM, Polyestyrene,
Polyethylene, Polyproplene, Polvinyl Chloride, Polyacylonitrite.

- Keep Container Closed,Store Cool And Well Ventilated, Open Slowly To Control Released Pressure.
- Keep Away From Flame, Direct Sunlight, Store Cool And Well Ventilated.
- Do Not Reuse Empty Containers W/OCleaning. Obserevs all Precautions For Empty Containers.

8. Exposure controls and personal protection

Engineering Control
Measures / Ventilation

Use Local Exhaust Ventilation To Control process.Provide Mechanical Ventilation Of
Confined Spaces. Use Explosion Proof Ventilation Equipment.

Occupational Expourse
Limits (OEL) Values

TWA; 50ppm (188mg/m⁰) (Skin) ACIGH (2000).

Personal Protection

Vapor Respirator, Gloves, Goggles, Full Suit, Footwear.

9. Physical and chemical properties

Physical State	: Liquid	Form / Color	: Clear Colorless
Odor	: Hydcarbon Odor	Odor Threshold	: N/A
Ph	: N/A	Freezing / Melting Point	: 95*c
Boiling Point Range	: 110-111* c	Flash Point (Tcc ASTM D 56)	: 5*c
Explosive Limits (In Air)	: 1.3-6.7 vol%	Vapor Presure (38*c)	: 7kPa
Auto Ignition Temperture	: >630* c	Density (15*c)	: 0.865 kg / dm

Specific Gravity (15.0 / 15.0)	: 0.865	Vapour Density (101.3kPa/air=1)	: >1.00
Solubility In Water (25*c)	: 0.05 WT%	Material Hydroscope	: No
Viscosity (26*c)	: 0.64cST	Evaporator Rate (n- Bu Acetate=1)	: 2,400
Coeff, Of Thermal Expansion (Liq)	: 0.00106*c	Moiecular Weight	: 92

10. Stability and reactivity

Hazardous Pollymerization: No Condition To Avoid Pollymerization : NA

Stability : Stable Condition To Avoid Instability : NA

Materials and Conditions To Avoid: Strong Oxidizing agents

Hazardous Docompositions Products : None

11. Toxicological information

Inhalation	Irritating to Eyes and Respiratory tract, diziness, central nervous System Effects. Negllgble Hazard between -18*c to 38*c
Skin Contact	Dry Skin, Low Order Of Toxicity.
Eye Contact	Cause Eyes Discomfort But Will Not Injure Eye Issue.
Ingestion	Minimal Toxicity, Small Amounts May Cause bronchpneumonia or Pulmonary edema.

12. Ecological information

Enviromental Mobility	Highly Volatile and Will rapidly evaporate To The air If rleased Into The Water.
Enviromental Degradability	Biodegrade Rapidly, Remove In Wastewalar Treatment Facility.
Ecotoxicity and Bioaccumulation	Expected to Be Harmful to Aquatic Organisms

13. Disposal considerations

- Combine With Other Materials To Indicate another Roule Of Disposal
- Recycle, Recover Or Dispose Empty Drums Through a Suitably Qualified Or Licenced Contractor.
- Ensure Compliance With National And Local Regulation.

- Not Suitable For Disposal either Landfill or via municipal sewers, Drains , Natural Streams or Rivers, This Product is ash less and can be burned directly in appropriate equipment.
- Contact Local Transmare Chemical Company Supplier Or Local Authorities for More Information.

14. Transport information

	Land	Sea	Air
Class	3	3	3
Pg	II	II	II
Un Number	1294	1294	1294
Subsidiary Risk	Nil	Nil	Nil
Transport Document Name	Toluene, Glass3, UN 1294, PG II, (5°C c.c.)	Toluene, Glass3, UN 1294, PG II, (5°C c.c.)	Toluene
Others	Hazchem Code : 3YE	Marine Pollutant : No EMS Number : F-E. S-D Risk Label 3	

15. Regulatory information

Classification And Labeling	Governing Directive : Dangerous Substances
Classification / Symbol : Highly Flammable / F	Directive 67 / 648 / EC
Classification / Symbol : Harmful / Xn	Label Name : Toluene
Nature Of Special Risk:	Safety Advise:
R11: Highly Flammable	S07 / 09 : Keep Container Close & Well Ventilated.
R20 Harmful By Inhalation	S16 : Keep Away From Sources Of Ignition.
	S25 : Avoid Eye Contact.
	S29 : Do Not Empty Into Drains.
	S33 : Take Precautionary Measures Against Static Discharges.
	S43A :In Case Of Fire, Use Sand, Earth, Chemical Powder Alcohol Type Foam.

16. Other information

Since 07 July 2007, This MSDS Has Been Revised In Section (s) 2, 14, 15. This Information Relateds Only To The Material Designated And May Not Be Valid For Such Information Is To The Best Of Knowledge And Believed Accurate And Reliable As Of The Date Indicated. However, no Representation, Warranty Or Guarantee Is Made as to Its Accuracy, Reliability of Completeness. It Is The User's Responsibility to satisfy himself as to the suitability and completeness of such Information for his Own Particular Use.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This document was generated automatically and may not reflect the latest formulation or regulatory revision. For the most up-to-date, accurate MSDS, please email us at muscatchem@gmail.com.