

RXSOL ORG - 4 Water Tank Cleaner

Part No. RXSOL-16-1080-035 — Generated 29 Sep 2026

1. Product and Company Identification

Product Name : RXSOL ORG - 4 35 KG

Product Type : RXSOL-16-1080-035

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone : +91 22 65113333 / 5555 / 9999 / 27611360

Fax : +91 22 2781 1318 ::AOH :0091 9821214367

Email : **123@rxmarine.com**

Website : www.rxmarine.com

2. Composition / information on ingredients

Chemical Name	Concentration	CAS Number	EC Number	R Phrases*	Symbols
Hydrogenated Mixture	MIXTURE 20%				
organic mixture	MIXTURE 38%				
Fatty Alcohol Ethoxylate	Mixture 42 %				

Mixture of the substances listed below with no hazardous additions.

Hydrogenated Mixture of C10-C13 organic solvents : Xn,65 Symbol: Xn, N

Fatty Alcohol Ethoxylate 34398-01-1 1 - 5 Xi,36/38 10-25% No Hazardous additions

Xn=Harmful, Xi=Irritant, N=Environmentally Harmful

3. Hazards Identification

Human Health Hazards R 36/38 Causes Irritation / Inhalation may cause headache & dizziness . may cause adverse effects to aquatic environment., Keep away from food, children , animal .

4. First Aid Measures

INHALATION supply fresh air on irritation medical attention require & show this MSDS to physician.

SKIN contact In case of contact with skin , wash immediately with plenty of water and soap Remove contaminated clothes. On extra irritation use ointment on Doctor advice.

EYE contact Flush with running water on open eyelids for at least 15 minutes, Immediately medical attention require.

INGESTION seek medical attention , don't try to drink more water / milk because too much water increase the danger of vomiting . (on vomiting always keep head low to prevent inhalation of airways)

5. Fire-fighting Measures

Suitable Water, fog or mist, alcohol-resistant foam, on small fires dry chemical, carbon dioxide (CO₂) also can be used. Not suitable Alcohol foam / and high pressure of water jet may cause splitting of excess materials.

Special container close to fire cooled immediately then remove to other place. Precaution for fire-fighters Self contained breathing apparatus or apparatus should be attached to air supply.

NOTE : fired materials vapours are heavier than air and may travel along the ground for to ignition sources, so try to move all sources to safe distance otherwise keep in cooling mode.

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTION

Direct flow into drainage system, surface or ground water is prohibited.

CLEANING METHOD

for preventing the spreading of materials remove spill mechanically or with absorbent materials and dispose of in accordance with section 13. Flush with large amounts of water to clean the area. Ventilate well.

Personal

During usage of chemical personal should use all normal protective equipment and avoid contact with eye and skin and for use in close environment personnel should use respiratory breathing apparatus.

7. Handling and Storage

Condition to Avoid

Flammable but product is stable under normal condition, take precaution as industrial chemical.

Materials to Avoid

Do not subject directly to ALKALINE / Acidic medium.

Handling Keep Container Tightly Closed in the original container and keep away from open flames / ignition sources

NOTE : Eyewash facilities require at workplace

- The product causes corrosion on skin and mucous membranes

GENERALLY PL. Note that in case of discharge of acidic or alkaline products into the sewerage system the pH must be in the range of 6-10 since higher or lower pH values may damage the sewerage system or impair biological dosage treatment plants. So that for maintaining pH we have to add acidic / basic medium neutraliser. For example if pH is less than 6 basic neutraliser is required and if pH is more than 10 acidic nature neutraliser is required. For details of any guideline pl. Visit our technical website www.rxmarine.com

- Dilute in water (always use plastic jar and RXSOL should be added to water never add water to RXSOL.)

8. Exposure controls and personal protection

Personal protection

Respiratory System Protection

Approved respirator must be worn when spraying otherwise normally not required

Eye Protection

if there is possibility to contact wear goggles for eye protection

Hand protection

wear PVC chemical resistance protective gloves

Other Information

smoking in store / work area is prohibited.

9. Physical and chemical properties

APPEARANCE

Clear liquid

DENSITY

g/cm³ at 15°C: 1.25

pH	ACIDIC
FLASH POINT	NA
Boiling point	110 °C
Ignition temp	N/A
SOLUBILITY	Emulsifiable with water

10. Stability and reactivity

Stable under normal condition on access of heat Vapour/gas may form explosive mixtures with air.

Hazardous Decomposition Products	No decomposition if stored and used as directed. In FIRE combustion CO, CO ₂ , NH ₃ , SOX etc hazardous gas produced.
----------------------------------	---

NOTE	AVOID CONTACT WITH ALKALINE SUBJECT / high temperature / fire .
------	---

Note	MATERIALS TO AVOID Hydrocarbons and their derivatives may attack certain types of plastic, rubber and paint.
------	--

11. Toxicological information

Skin Irritation	Gives irritation may causes dryness. And prolonged contact with skin can cause degreasing effect.
-----------------	---

Eye Irritat	Cause severe irritation
-------------	-------------------------

Sensitization	Sensitizing properties not known
---------------	----------------------------------

Chronic Toxicity	Not Identified
------------------	----------------

Carcinogenicity	Not regulated. (prolonged inhalation of solvents may cause chronic solvent intoxication.
-----------------	---

12. Ecological information

RXSOL-16-1080-035 no enviromental problem will create when the product is used correctly . in its intended use the product will not be released into the environment.

13. Disposal considerations

As per guide line of local rules and regulation and before disposal and neutralization pl. refer 07 article..

14. Transport information

Goods classified for road / rail / sea transport : YES with UN-no: : 3082
Proper shipping name: contains Sulfamic
Hazard identification no.: 90 Product identification (UN) no.: 3082
TREM CARD no. CEFIC: 90G01
Marine pollutant: No
Flash point : NA
Label colour : White./Black.

15. Regulatory information

Symbols	Xn, N
Contains	Sulfamic
R-phrases	Non Toxic to aquatic organisms
R-65 Harmful	May cause lung damage if swallowed
S-phrases	S-23 Do not breathe vapour S-24 Avoid contact with skin S-60 This material and its container must be disposed of as hazardous waste S-61 Avoid spillage to the environment. Ask for special instructions/safety
Datasheet	S-62 If swallowed, do not induce vomiting; seek medical advice immediately S-36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
REFERENCES	Classified according to European directive on classification of dangerous preparations 90/492/EEC and accordance with EU directive 88/379. .

16. Other information

On the basis of information and experience as well as our present knowledge this guidelines is only safe for handling, use, processing, storage, transport, disposal and discharge; this is not a guarantee or quality of specification. And combination with other products will lost the properties. It is always the responsibility of the user to take all necessary steps to ensure that information given here is read and understood by all who use, handle, dispose of or in any way come in contact with the product. It is not to be considered as a guarantee of the products properties. Disclaimer::: The information in this MSDS is meant as a description of the safety requirements of our product.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.