

Paraffin Inhibitor RXSOL 3085

Part No. RXSOL-81-2225-210 — Generated 06 Oct 2026

1. Product and Company Identification

Product Name : Paraffin Inhibitor RXSOL 3085
Part Number : RXSOL-81-2225-210

Company Details:
RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN, Kenya, CANADA

Phone +91 22 27815540 / 41 / 42
Fax +91 22 2761 2100 :::AOH :0091 9821214367
Email 123@rxmarine.com
Website www.rxmarine.com

2. Composition / informationon ingredients

Name of Substance	Cas Number	EC No	Wt. %	Symbol
Xylene	1330-20-7	202-422-2	70 -80%	Xi
Ethylbenzene	100-41-4	202-849-4	10-20%	Xn
Acetic acid	64-19-7	100-580-7	5 - 10%	Xn
Alkylarylsulfonic acid	68411-32-5	271-117-1	1 -5 %	Xn
Proprietary Blend	---	---	5-10%	---

3. Hazards Identification

Signal Word	Danger
Hazard Statements	Flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes severe skin burns and eye damage. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. (hearing organs)
Precautionary statements - prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take all other precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Precautionary statements - response	Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
	Storage: Store locked up. Store in a well-ventilated place. Keep cool. Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

4. First Aid Measures

Eye Contact	Get medical attention immediately. Call a poison center or physician. Immediately flush the eye(s) continuously with lukewarm, gently flowing water for at least 20-60 minutes while holding the eyelid(s) open. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician
Skin Contact	Get medical attention immediately. Call a poison center or physician. Wash affected area with soap and mild detergent for at least 20 - 60 minutes. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.
Ingestion:	Call a poison center or physician. Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway
Note to Physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

5. Fire-fighting Measures

Suitable extinguishing media	Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	Do not use water jet
Protective Equipment	Wear suitable fire fighting suit.
Specific hazards arising from the chemical	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion
Hazardous thermal decomposition products	Carbon dioxide, carbon monoxide, sulfur oxides

Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	For non-emergency : personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
Environmental Precaution	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning up	Small Spill :: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large Spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and Storage

Advice on safe handling	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Storage	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use

8. Exposure controls and personal protection

Ingredient Name	Exposure Limits
-----------------	-----------------

Xylene	ACGIH TLV (United States, 3/2018).
	STEL: 651 mg/m ³ , 0 times per shift, 15 minutes.
	STEL: 150 ppm, 0 times per shift, 15 minutes.
	TWA: 434 mg/m ³ , 0 times per shift, 8 hours.
	TWA: 100 ppm, 0 times per shift, 8 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 435 mg/m ³ , 0 times per shift, 8 hours.
	TWA: 100 ppm, 0 times per shift, 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	STEL: 655 mg/m ³ , 0 times per shift, 15 minutes.
	STEL: 150 ppm, 0 times per shift, 15 minutes.
	TWA: 435 mg/m ³ , 0 times per shift, 8 hours.
	TWA: 100 ppm, 0 times per shift, 8 hours.

Ethylbenzene	ACGIH TLV (United States, 3/2018).
	TWA: 20 ppm, 0 times per shift, 8 hours.
	NIOSH REL (United States, 10/2016).
	STEL: 545 mg/m ³ , 0 times per shift, 15 minutes.
	STEL: 125 ppm, 0 times per shift, 15 minutes.
	TWA: 435 mg/m ³ , 0 times per shift, 10 hours.
	TWA: 100 ppm, 0 times per shift, 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 435 mg/m ³ , 0 times per shift, 8 hours.
	TWA: 100 ppm, 0 times per shift, 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	STEL: 545 mg/m ³ , 0 times per shift, 15 minutes.
	STEL: 125 ppm, 0 times per shift, 15 minutes.
	TWA: 435 mg/m ³ , 0 times per shift, 8 hours.
TWA: 100 ppm, 0 times per shift, 8 hours.	

Acetic Acid	ACGIH TLV (United States, 3/2018).
	STEL: 37 mg/m ³ , 0 times per shift, 15 minutes.
	STEL: 15 ppm, 0 times per shift, 15 minutes.
	TWA: 25 mg/m ³ , 0 times per shift, 8 hours.
	TWA: 10 ppm, 0 times per shift, 8 hours.
	NIOSH REL (United States, 10/2016).
	STEL: 37 mg/m ³ , 0 times per shift, 15 minutes.
	STEL: 15 ppm, 0 times per shift, 15 minutes.
	TWA: 25 mg/m ³ , 0 times per shift, 10 hours.
	TWA: 10 ppm, 0 times per shift, 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 25 mg/m ³ , 0 times per shift, 8 hours.
	TWA: 10 ppm, 0 times per shift, 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
TWA: 25 mg/m ³ , 0 times per shift, 8 hours	

Alkylarylsulfonic acid	TWA: 10 ppm, 0 times per shift, 8 hours.
	None.

Consult local authorities for acceptable exposure limits.

If OSHA permissible exposure levels are shown above they are the OSHA 1989 levels or are from subsequent OSHA regulatory actions.

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Engineering Controls

Personal Protection	Eye protection : Wear chemical safety goggles. When transferring material wear face-shield in addition to chemical safety goggles. If inhalation hazards exist, a full-face respirator may be required instead.
	Hand protection : Chemical-resistant glove
	Skin protection : Wear long sleeves and chemical resistant apron to prevent repeated or prolonged skin contact.
Hygiene measures	Respiratory protection : If a risk assessment indicates it is necessary, use a properly fitted, air purifying or supplied air respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
	
Gloves	Suit

9. Physical and chemical properties

Physical State	Liquid
Colour	Pale yellow
Odour	Aromatic.
Odor threshold	Not Available
pH	2 - 4 5% of product in 75% isopropanol / 25% water solution
Boiling Point	Not Available
Initial Boiling Point	Not Available
Freezing Point/ Melting Point	Not Available
Flash Point	Closed cup: 28.89°C (84°F)
Burning Time	Not Applicable
Burning Rate	Not Applicable
Evaporation rate	Not Applicable
Flammability (solid, gas)	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Upper explosion limit	No data available
Lower explosion limit	No data available
Explosive properties	No data available
Vapor pressure	22.1 kPa (165.5 mm Hg, 3.2 psig) @ 54.4°C, 130 F (Reid)
Vapor density	No information available
Relative density	0.88

Density	0.886 g/cm ³
Water solubility	insoluble
Partition coefficient: octanol	No data available
Autoignition temperature	No data available
Thermal decomposition	No data available
Viscosity, kinematic	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Dynamic viscosity	No data available
VOC (%)	No data available
Pour point	No information available

10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Stability	Stable under normal conditions and recommended use.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials, organic materials, and alkalis.
Hazardous Decomposition	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Condition to Avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, grind or expose containers to heat or sources of ignition.
Polymerization	Hazardous polymerization does not occur.

11. Toxicological information

	Product/ingredient name	Result	Species	Dose	Exposure	
Acute toxicity	Xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours	
		LD50 Dermal	Rabbit	>1700mg/kg	--	
		LD50 Oral	Male Rat	3523 mg/kg	--	
		LD50 Oral	Rate	4300 mg/kg	--	
		LD50 Oral				
	Ethylbenzene	LD50 Dermal	Rabbit	15400 mg/kg	--	
		LD50 Oral	Rat	3500 mg/kg	--	
	Acetic Acid	LC50 Inhalation Vapor	Rat	11000 mg/m³	4 hours	
		LD50 Dermal	Rabbit	1060 mg/kg	---	
Alkylarylsulfonic acid	LD50 Oral	Rat	3310 mg/kg	--		
	LD50 Oral	Rat	1260 mg/kg	--		
Irritation/Corrosion	No applicable toxicity data					
Sensitization	No applicable toxicity data					
Mutagenicity	No applicable toxicity data.					
Carcinogenicity	Product/ingredient name			OSHA	IARC	NTP
	Xylene			-	3	-
	Ethylbenzen			-	2b	-
Reproductive toxicity	No applicable toxicity data					
Teratogenicity	No applicable toxicity data					
Specific target organ toxicity (single exposure)	Name	Category	Route of exposure		Target organs	
	Xylene	Category 3	Not applicable.		Narcotic effects	
Specific target organ toxicity (repeated exposure)	Name	Category	Route of exposure		Target organs	
	Ethylbenzene	Category 2	Not determined		Hearing organs	
Aspiration hazard	Name	Result				
	Xylene	ASPIRATION HAZARD - Category 1				
Information on the likely routes of exposure	Routes of entry anticipated: Dermal, Inhalation.					
Potential acute health effects						

Eye contact :	Causes serious eye damage.	
Inhalation :	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.	
Skin contact :	Causes severe burns. Harmful in contact with skin.	
Ingestion :	Can cause central nervous system (CNS) depression.	
Potential chronic health effects		
General :	May cause damage to organs through prolonged or repeated exposure.	
Carcinogenicity :	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.	
Mutagenicity :	No known significant effects or critical hazards.	
Teratogenicity :	No known significant effects or critical hazards.	
Developmental effects :	No known significant effects or critical hazards.	
Fertility effects :	No known significant effects or critical hazards.	
Acute toxicity estimates	Route	ATE Value
	Oral	3900.7 mg/kg
	Dermal	1471.1 mg/kg
	Inhalation (gases)	6686.8 ppm
	Inhalation (vapors)	84.49 mg/l

12. Ecological information

	Product/ingredient name	Result	Species	Exposure
Toxicity	Xylene	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 Hours
		Acute LC50 13400 µg/l Fresh water		
	Ethylbenzene	Acute EC50 4600 µg/l Fresh water	Fish - Pimephales promelas	
		Acute EC50 2930 to 4400 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 Hours
		Acute LC50 5200 µg/l Marine water	Daphnia - Daphnia magna	72 hours
		Acute LC50 5200 µg/l Marine water	Crustaceans - Americamysis bahia	48 Hours
		Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
		Chronic NOEC 1000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
		Acute EC50 73400 µg/l Fresh water		
		Acute EC50 65000 µg/l Fresh water	Algae - Navicula seminulum	96 hours
		Acute LC50 50.1 µl/L Marine water	Daphnia - Daphnia magna	48 hours
		Acute LC50 50.1 µl/L Marine water	Crustaceans - Artemia sp.	48 hours
		Acute LC50 75000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
Persistence and degradability	Not available.			
Other adverse effects	No known significant effects or critical hazards.			

Persistence and degradability

Results of PBT and vPvB
assessment

Not classified as PBT/vPvB by current EU criteria.

13. Disposal considerations

Remarks Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Waste Disposal Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

			DOT	TDG Classification	IMDG	IATA
	UN	Number	UN2924	UN2924	UN2924	UN2924
Transport hazard class(es)	Proper shipping name		FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Contains: Xylene, Alkylarylsulfonic acid)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Contains: Xylene, Alkylarylsulfonic acid)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Contains: Xylene, Alkylarylsulfonic acid)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Contains: Xylene, Alkylarylsulfonic acid)
	Transport hazard class(es)		3 (8)	3 (8)	3 (8)	3 (8)
	Packing Group		III	III	III	III
	Environmental hazards		NO	NO	NO	NO

Additional information

ADR/RID Reportable quantity 133.69 lbs / 60.695 kg [18.22 gal / 68.972 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

TDG Classification Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.40-2.42 (Class 8).

IATA The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Environmental hazards

Environmental hazards No

Marine pollutant No

15. Regulatory information

US Federal Regulations	TSCA 12(b) one-time export: No products were found. TSCA 12(b) annual export notification: No products were found. United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: Ethylbenzene; Toluene; Benzene Clean Water Act (CWA) 311: Ethylbenzene; Xylene; Toluene; Benzene; Acetic acid; Sulfuric acid
CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) :	This product contains substance(s) which are not listed on the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).
NATIONAL REGULATIONS, CANADA :	WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS) : This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.
WHMIS CLASSIFICATION :	B2 - Flammable Liquids, D2A - Materials Causing Other Toxic Effects - Very Toxic Material, D2B - Materials Causing Other Toxic Effects - Toxic Material
California Prop. 65	WARNING: This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Sulfuric acid, ethylbenzene, cumene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm.

16. Other information

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	--