

Safe Parts Washing Solvent

Part No. RXSOL-10-1728-025 — Generated 29 Sep 2026

1. Product and Company Identification

Product Name RXSOL-10-1728

Product Type Safe Parts Washing Solvent >140°F

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Vizag, Fujairah, Muscat

Phone +91 22 65113333 / 5555 / 9999 / 27611360

Fax +91 22 2781 1318 ::::AOH :0091 9821214367

Email mail@rxmarine.com

2. Composition / informationon ingredients

COMPON E N T S - C H E M I C A L N A M E S A N D COMMON N A M E S (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	Applicable PEL-OSHA	Exposure Limits TLVACGIH	Carcinogen Ref. Source **
Petroleum Di s t i l l a t e s	64742-88-7	No	N/E	N/E	d

3. Hazards Identification

PRIMARY ROUTES OF ENTRY: [] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS

ACUTE EFFECTS Toxicity: CNS depression producing headache, dizziness, nausea and loss of consciousness.

Inhalation: High concentrations or prolonged exposure to lower concentrations may be slightly irritating to mucous membranes.

Eye Contact: Slight irritation from short term contact. Prolonged & repeated contact more irritating.

Skin Contact: Prolonged & repeated liquid contact may result in irritation and dermatitis.

Ingestion:	May result in vomiting. Aspiration of vomitus into lungs must be avoided as lung contact can result in chemical pneumonitis and pulmonary edema.
CHRONIC EFFECTS:	None known.
Medical Conditions	
Generally Aggravated by Exposure:	Pre-existing irritation of skin or mucous membranes.

4. First Aid Measures

Eye Contact:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin Contact:	Wash with soap and water. If irritation persists, get medical attention.
Inhalation:	Remove to fresh air. Provide oxygen if breathing is difficult. Get medical attention.
Ingestion:	DO NOT INDUCE VOMITING. Drink 3 to 4 glasses of water. Get immediate medical attention.

5. Fire-fighting Measures

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols)	N/A
Auto Ignition Temperature	N/D
Flammability Limits in Air by % in Volume:	
% LEL:	1
% UEL:	6
FLASH POINT AND METHOD USED (non-aerosols):	145°F TCC
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire space without proper protective equipment including NIOSH approved self-contained breathing apparatus. Cool fire exposed containers, surrounding equipment & structures with water.
EXTINGUISHER MEDIA:	Water spray or fog, foam, dry chemical or CO2. Do not use direct water stream.
Unusual Fire & Explosion Hazards:	None known.

6. Accidental Release Measures

7. Handling and Storage

Steps To Be Taken If Material Is Spilled Or Released:	Contain spill. Keep out of surface waters & any sewers or water courses entering or leading to surface waters. Soak up with inert absorbent & place in properly labeled leak-proof containers for disposal.
---	---

Waste Disposal Methods:	Dispose of in accordance with all local, state and federal regulations.
Precautions To Be Taken In Handling & Storage:	in original shipping containers away from heat, open flame & oxidizing materials. Keep closed when not in use. Shelf life 1 year.
Other Precautions &/or Special Hazards:	KEEP OUT OF REACH OF CHILDREN. Read & follow label directions.

8. Exposure controls and personal protection

Respiratory Protection (specify type):	As required to prevent overexposure. NIOSH approved air purifying respirator for organic vapors or atmospheresupplying respirator.
Protective Gloves:	As required to minimize skin contact.
Eye Protection:	Safety glasses or goggles.
Ventilation Requirements:	Explosion proof ventilation as required to control vapor concentrations
Other Protective Clothing & Equipment:	Clothing as required to minimize skin contact. Eyewash station and safety shower.
Hygienic Work Practices:	Do not eat, drink or smoke in work area. Wash hands after handling.

9. Physical and chemical properties

Boiling Point:	300°F
Specific Gravity (H2O=1):	0.78
Vapor Pressure:	PSIG @ 70°F (Aerosols) : N/A
Vapor Pressure (Non-Aerosols)(mm Hg and Temperature):	5@100°F
Vapor Density (Air = 1):	5
Evaporation Rate (= 1) :	N/D
Solubility in Water:	Negligible
Water Reactive:	No
Appearance and Odor:	liquid with typical petroleum odor

10. Stability and reactivity

STABILITY ☒ STABLE ☐ UNSTABLE

HAZARDOUS
POLYMERIZATION [] WILL [X] WILL NOT OCCUR

Incompatibility (Mat. to avoid): Oxidizing materials.

Conditions to Avoid: Heat, sparks, open flame.

Hazardous
Decomposition Products: Oxides of carbon & unidentified organics may be formed during combustion

11. Toxicological information

12. Ecological information

13. Disposal considerations

14. Transport information

15. Regulatory information

16. Other information

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This document was generated automatically and may not reflect the latest formulation or regulatory revision. For the most up-to-date, accurate MSDS, please email us at muscatchem@gmail.com.